

<b>Model Variations</b>	CS2740-BK
<b>Panel Type</b>	IPS
<b>Backlight</b>	Wide-Gamut LED
<b>Size</b>	26.9" / 68.4 cm
<b>Native Resolution</b>	3840 x 2160 (16:9 aspect ratio)
<b>Viewable Image Size (H x V)</b>	596.2 x 335.3 mm
<b>Pixel Pitch</b>	0.155 x 0.155 mm
<b>Pixel Density</b>	164ppi
<b>Grayscale Tones</b>	1,024 tones (a palette of 65 thousand tones)
<b>Display Colors</b>	1.07 billion from a palette of 278 trillion
<b>Viewing Angles (H / V, typical)</b>	178°, 178°
<b>Brightness (typical)</b>	350 cd/m <sup>2</sup>
<b>Contrast Ratio (typical)</b>	1000:1
<b>Response Time (typical)</b>	10 ms (gray-to-gray)
<b>Color Gamut (typical)</b>	Adobe RGB: 99%
<b>Video Signals</b>	
<b>Input Terminals</b>	USB Type-C (DisplayPort Alt Mode, HDCP 1.3), DisplayPort (HDCP 1.3), HDMI (Deep Color, HDCP 2.2 / 1.4)
<b>Digital Scanning Frequency (H / V)</b>	USB Type-C, DisplayPort: 25 – 137 kHz, 23 – 61 Hz
	HDMI: 15 – 135 kHz, 23 – 61 Hz
<b>USB</b>	
<b>Upstream</b>	USB 3.1 Gen 1: Type-C (DisplayPort Alt Mode, Power Delivery Source 60 W max.), USB 3.1 Gen 1: Type-B
<b>Downstream</b>	USB 3.1 Gen 1: Type-A x 2
<b>Power</b>	
<b>Power Requirements</b>	USB 2.0: Type-A x 2
<b>Typical Power Consumption</b>	USB 2.0: Type-A x 2
<b>Maximum Power Consumption</b>	USB 2.0: Type-A x 2
<b>Power Save Mode</b>	1.0 W or less
<b>Standby Mode</b>	1.0 W or less
<b>Features &amp; Functions</b>	
<b>Digital Uniformity Equalizer</b>	Yes
<b>Preset Modes</b>	Color Mode (User, Adobe RGB, sRGB, Calibration)
<b>OSD Languages</b>	English, German, French, Italian, Japanese, Simplified Chinese, Spanish, Swedish,

Traditional Chinese

**Others**

Color Adjustment, Input Color Format, YUV Color Matrix, Input Range, Noise Reduction, I/P Conversion, Picture Expansion, Menu Rotation, Power Save, Input Skip, Mode Skip, Custom Key, Information Display, Key Lock, DUE Priority

**Physical Specifications**

<b>Dimensions (Landscape, W x H x D)</b>	638 x 404.1 – 559.1 x 265 mm
<b>Dimensions (Portrait, W x H x D)</b>	378.2 x 649 – 689 x 265 mm
<b>Dimensions (Without Stand, W x H x D)</b>	638 x 378.2 x 75 mm
<b>Net Weight</b>	10.3 kg
<b>Net Weight (Without Stand)</b>	6.7 kg
<b>Height Adjustment Range</b>	155 mm
<b>Tilt</b>	35° Up, 5° Down
<b>Swivel</b>	344°
<b>Pivot</b>	90°
<b>Hole Spacing (VESA Standard)</b>	100 x 100 mm
<b>Environmental Requirements</b>	
<b>Operating Temperature</b>	0 – 35 °C
<b>Operating Humidity (R.H., non condensing)</b>	20 – 80 %
<b>Certifications &amp; Standards (Please contact EIZO for the latest information.)</b>	CB, CE, TUV/GS, cTUVus, FCC-B, CAN ICES-3 (B), TUV/S, PSE, VCCI-B, RCM, EAC, RoHS, WEEE, TUV/Ergonomics
<b>Dedicated Software</b>	
<b>Easy Screen-to-Print Color Matching Tool Quick Color Match</b>	Supported
<b>Proprietary Software</b>	
<b>Color Management Software ColorNavigator 7</b>	Supported
<b>Supplied Accessories (May vary by country. Please contact EIZO for details.)</b>	
<b>Signal Cables</b>	USB Type-C (2 m), DisplayPort (2 m)
<b>Others</b>	AC power cord, USB cable, Setup guide, Warranty card